

Endura Super Durable Matt

DESCRIPTION

Johnstone's Super Durable Matt offers ultimate durability, tested to over 10,000 scrubs. For use on interior walls and woodwork, it's tougher than Acrylic Eggshell, making it easier to clean and the ideal solution for high traffic areas. A fast drying, low odour dead flat matt finish ideal for use where durability and performance is important.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Interior walls and ceilings. Suitably primed woodwork and radiators.

COLOUR RANGE

Available in Brilliant White, Magnolia and L Base. Over 7000 colours are available via the Johnstone's CMS 2010 Tinting System.

FINISH

Matt.

VOLUME SOLID

35%

COVERAGE



Approximately 11-13 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME



Touch dry in 1-2 hours. Recoatable after 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3-7.99% VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/a): 30g/l (2010). This product contains max 15g/l VOC.

FILM THICKNESS

Wet: 83µm, dry: 29µm.

KEY PROPERTIES

- Ultimate durability and performance.
- Class 1 ISO11998 & Class C BS Scrub Rating.
- Ideal for high wear/traffic areas.
- Dead flat matt finish.

PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any crazed or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstones Joncryn Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For further advice contact PPG Extra. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Endura Super Durable Matt. Prime bare timber and metal surfaces with an appropriate Johnstones primer. Allow radiators to cool before painting. For additional information and free Johnstones Trade datasheets call 01924 354945 or visit www.johnstonstrade.com

APPLICATION



Stir well before use and apply by brush, roller or paint pad. Also suitable for applying by spray. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading.

CLEANING



Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty wastes paint into drains or watercourses.

PRECAUTIONS

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- When spraying do not breathe spray, wear suitable respiratory protective equipment.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

SIZES

5 Litre only.

PROFESSIONAL DECORATORS

Safety sheet available for professional user on request.